

Model: 01-1342-0000
KUH Custom Towbar



09/2011 – Rev. 02

For Spare Parts, Operations & Service Manuals or Service Needs
Scan the QR code or visit Tronair.com/aftermarket



REVISION	DATE	TEXT AFFECTED
01	03/2010	Original release
02	09/2011	Modified Parts List

TABLE OF CONTENTS

PAGE

1.0	PRODUCT INFORMATION	1
1.1	DESCRIPTION.....	1
1.2	MODEL & SERIAL NUMBER.....	1
1.3	MANUFACTURER.....	1
1.4	SPECIFICATIONS	1
2.0	SAFETY INFORMATION.....	1
2.1	GENERAL.....	1
3.0	TRAINING.....	1
3.1	TRAINING REQUIREMENTS	1
3.2	TRAINING PROGRAM	1
3.3	OPERATOR TRAINING.....	1
4.0	ASSEMBLY INSTRUCTIONS.....	1
4.1	HEAD ASSEMBLY.....	1
5.0	OPERATION.....	2
5.1	LANDING GEAR ASSEMBLY.....	2
5.2	PRELIMINARY CHECKLIST.....	2
5.2.1	Towbar.....	2
5.3	USAGE PROCEDURE.....	2
5.3.1	Aircraft Attachment.....	2
5.3.2	Tug Attachment.....	2
5.3.3	Couplers.....	3
5.3.4	Towing Operation.....	3
6.0	PROVISION OF SPARES.....	4
6.1	SOURCE OF SPARE PARTS.....	4
6.2	RECOMMENDED SPARE PARTS LISTS	4
7.0	IN-SERVICE SUPPORT.....	4
8.0	GUARANTEES/LIMITATION OF LIABILITY	4

Tronair towbars/heads must only be used with matching Tronair heads/towbars, and Tronair shear pins.

This product can not be modified without the written approval of Tronair, Inc. Any modifications done without written approval voids all warranties and releases Tronair, Inc., its suppliers, distributors, employees, or financial institutions from any liability from consequences that may occur. Only Tronair OEM replacement parts shall be used.

1.0 PRODUCT INFORMATION

1.1 DESCRIPTION

The Tronair Model 01-1342-0000 Custom Towbar is designed for towing the KUH (Korean Utility Helicopter) manufactured by Korea Aerospace Industry (KAI).

1.2 MODEL & SERIAL NUMBER

Reference nameplate on unit

1.3 MANUFACTURER

TRONAIR , Inc. 1 Air Cargo Pkwy East Swanton, Ohio 43558 USA	Telephone: (419) 866-6301 or 800-426-6301 Fax: (419) 867-0634 E-mail: sales@tronair.com
---	---

1.4 SPECIFICATIONS

Aircraft Application	KUH manufactured by KAI
Maximum Aircraft Gross Weight.....	17,000 lbs (7.1 Metric ton)
Length	155 in (393.7 cm) From eyebolt centerline to centerline attachment
Width	31 ¹⁵ / ₁₆ in (81.1 cm)
Height.....	6 ⁹ / ₁₆ in (16.7 cm) From ground to towbar tube centerline.
Weight.....	155 lbs (70.3 kg)
Finish.....	Blue Powder Coat
Material	Steel

2.0 SAFETY INFORMATION

2.1 GENERAL

The Tronair Model 01-1342-0000 Custom Towbar is used for moving KUH only.

To ensure safe operation, please read the following statements and understand their meaning. This manual contains safety precautions which are explained as follows. Please read carefully.



WARNING! Warning is used to indicate the presence of a hazard that can cause **severe personal injury, death, and/or substantial property damage** if the Warning Notice is ignored.

CAUTION! Caution is used to indicate the presence of a hazard which will or can cause **minor personal injury or property damage** if the Caution Notice is ignored.

3.0 TRAINING

3.1 TRAINING REQUIREMENTS

The employer of the operator is responsible for providing a training program sufficient for the safe operation of the towbar.

3.2 TRAINING PROGRAM

The employer provided operator training program should cover safety procedures concerning use of the towbar in and around the aircraft at the servicing location.

3.3 OPERATOR TRAINING


The operator training should provide the required training for safe operation of the towbar.

NOTE: Maintenance and Trouble Shooting are to be performed by the skilled and trained technician.

4.0 ASSEMBLY INSTRUCTIONS

4.1 HEAD ASSEMBLY

Torque mounting bolts to 40 ft-lbs (54.2 N-m)



5.0 OPERATION

5.1 LANDING GEAR ASSEMBLY

Place landing gear assembly in desired location. Torque clamp nuts to 35 ft-lbs (47.5 N-m).

5.2 PRELIMINARY CHECKLIST

5.2.1 Towbar

- Check towing eye mounting bolts. Ensure the fasteners are not loose or missing.
- Check towing eye for bending, excessive wear and deformity.
- Check the ball lok-T pin. Ensure ball lok-T pin is securely attached to towbar via its lanyard. Ensure ball lok-T pin is not missing.



WARNING!

A damaged or bent towbar should not be used. Towbar should be repaired or replaced.



WARNING!

Towbars should be used with category 1 tugs ONLY in accordance with AHM 995 "Functional specifications for an aircraft tractor" Using a category 2 or higher tug may result in excessive loads and stresses being applied to the towbar and/or the aircraft. These excessive loads may cause failure of the towbar which could cause damage to the aircraft or personal injury.

5.3 USAGE PROCEDURE

5.3.1 Aircraft Attachment



CAUTION!

It is recommended that your towbar to attached to the aircraft first, and then connected to the tug to avoid possible aircraft damage.


5.3.2 Tug Attachment




CAUTION!

Damage to the towbar or aircraft can result from an excessive towbar angle during towing operations. Reference Figure 1.

- Use a pintle height so that the towbar is as level as possible during towing. Also, the pintle hook height should prevent contact of the towbar with the ground during towing.



Incorrect
Excessive Towbar Angle



Correct

FIGURE 1

5.3.3 Couplers



CAUTION!

Damage to the towbar or aircraft can result while towing with the following types of couplers:

- Lift Head
- Swivel Hook
- Vertical Side Swing Latch
- Standard Duty Latch

The couplers listed above are known to cause binding and failure in the lunette eye. Indicators of binding are wear on outside diameter of the eyebolt and indentation on the inside diameter of the eyebolt. **Reference Figure 2.**




FIGURE 2




FIGURE 3
 01-1950-5000 Standard Telecoupler

Tronair recommends a telecoupler pintle hook arrangement. This arrangement is known to eliminate binding. Tronair offers a Standard Telecoupler, Model Number 01-1950-5000, for use on tugs. **Reference Figure 3.**

Damage to the towbar and/or aircraft can result by towing or pushing an aircraft with an incorrect size eyebolt or pintle pin. A correct size eyebolt will make contact with the pintle pin. A gap between the eyebolt outside diameter and the coupler face plate should be easily seen. An eyebolt which is too large will cause the eyebolt to make contact with the face plate of the coupler. When the eyebolt is too large for the coupler, a gap between the inside diameter of the eyebolt and the coupler face plate will be seen. **Reference Figure 4.**

To ensure proper towing and pushing, check to make sure the pintle pin diameter is not too long for the eyebolt's inside diameter. An approximate one-half inch ($\frac{1}{2}$ ") gap between the pin diameter and the eyebolt should be seen. If any of these conditions are not met, please contact Tronair for information to obtain a new coupler.




FIGURE 4

5.3.4 Towing Operation

Damage to the towbar or aircraft can result from pushing an aircraft while maintaining too sharp of an angle between the tug and the aircraft. Contact between the towbar weldment and the tug must be avoided. It is recommended that the angle between the tug and towbar not exceed 90°. **Reference Figure 5.**




FIGURE 5

6.0 PROVISION OF SPARES**6.1 SOURCE OF SPARE PARTS**

Spare parts may be obtained from the manufacturer:

TRONAIR, Inc.	Telephone: (419) 866-6301 or 800-426-6301
1 Air Cargo Pkwy East	Fax: (419) 867-0634
Swanton, Ohio 43558 USA	E-mail: sales@tronair.com
	Website: www.tronair.com

For Spare Parts, Operations & Service Manuals or Service Needs:
Scan the QR code or visit Tronair.com/aftermarket

**6.2 RECOMMENDED SPARE PARTS LISTS**

Reference the following page(s) for Replacement Parts and Kits available.

Recommended Spares to be kept on hand:

G-1310-0418 ... Ball Lok-T Pin
H-3309 Shear Pin
H-3310 Shear Pin
U-1152 Foam Filled Tire

7.0 IN-SERVICE SUPPORT

Contact Tronair, Inc. for technical services and information. See Section 1.3 – Manufacturer.

8.0 GUARANTEES/LIMITATION OF LIABILITY

Tronair products are warranted to be free of manufacturing or material defects for a period of one year after shipment to the original customer. This is solely limited to the repair or replacement of defective components. This warranty does not cover the following items:

- Parts required for normal maintenance
- Parts covered by a component manufacturers warranty
- Replacement parts have a 90-day warranty from date of shipment

If you have a problem that may require service, contact Tronair immediately. Do not attempt to repair or disassemble a product without first contacting Tronair, any action may affect warranty coverage. When you contact Tronair be prepared to provide the following information:


- Product Model Number
- Product Serial Number
- Description of the problem

If warranty coverage is approved, either replacement parts will be sent or the product will have to be returned to Tronair for repairs. If the product is to be returned, a Return Material Authorization (RMA) number will be issued for reference purposes on any shipping documents. Failure to obtain a RMA in advance of returning an item will result in a service fee. A decision on the extent of warranty coverage on returned products is reserved pending inspection at Tronair. Any shipments to Tronair must be shipped freight prepaid. Freight costs on shipments to customers will be paid by Tronair on any warranty claims only. Any unauthorized modification of the Tronair products or use of the Tronair products in violation of cautions and warnings in any manual (including updates) or safety bulletins published or delivered by Tronair will immediately void any warranty, express or implied.

The obligations of Tronair expressly stated herein are in lieu of all other warranties or conditions expressed or implied. **Any unauthorized modification of the Tronair products or use of the Tronair products in violations of cautions and warnings in any manual (including updates) or safety bulletins published or delivered by Tronair will immediately void any warranty, express or implied and Tronair disclaims any and all liability for injury (WITHOUT LIMITATION and including DEATH), loss or damage arising from or relating to such misuse.**

Parts List

When ordering replacement parts/kits, please specify model, serial number and color of your unit.




Item	Part Number	Description	Qty
1	Z-7278	Assembly, Shock	

Item 1 consists of items which are not sold separately. Due to the high compression used in assembly, it is suggested this Shock Assembly be returned to Tronair for repair. Discuss with your salesperson.

2	H-3309	Assembly, Shear Pin	1
3	Z-7277-01	Machining, Towbar	1
4	J-4639-01	Plate, Landing Gear	1
5	Z-7663	Assembly, Landing Gear	1
6	G-1100-107544	Bolt, Hex Head, Grade 5, $\frac{3}{8}$ -24 x 4 $\frac{1}{2}$ " long	4
7	G-1250-1070N	Flatwasher, $\frac{3}{8}$ Narrow	10
8	G-1202-1075	Stopnut, $\frac{3}{8}$ - 24 Elastic	8
9	G-1100-107516	Bolt, Hex Head, Grade 5, $\frac{3}{8}$ -24 x 1 $\frac{3}{4}$ " long	4
10	X-1203	Assembly, Head	1
11	U-1152	Wheel, Foam Filled Tire	2
12	Z-5643-01	Weldment, Axle Mounting	1
13	G-1203-1105	Jamnut, $\frac{5}{8}$ - 18 Elastic	2
14	G-1250-1100N	Flatwasher, $\frac{5}{8}$ Narrow	4

Parts List

When ordering replacement parts/kits, please specify model, serial number and color of your unit.



Item	Part Number	Description	Qty
	X-1203	Assembly, Head; consists of:	
15	Z-7276-01	Weldment, Head	1
16	H-3310	Assembly, Shear Pin	2
17	R-2515	Pin, Sliding	1
18	G-1310-0418	Pin, T-Handle Ball Lock	1
19	G-1351-04	Rivet, Open End, Steel	1
20	G-1150-103503	Screw, Hex Head, Machine #10 – 32 x ³ / ₈ long	1
21	H-1026*07.0	Assembly, Lanyard	1



APPENDIX II

Declaration of Conformity



DECLARATION of CONFORMITY

The design, development and manufacture is in accordance with European Community guidelines

Custom Towbar
01-1342-0000

Relevant provisions complied with by the machinery:
2006/42/EC

Relevant standards complied with by the machinery:
EN ISO 12100-1

Identification of person empowered to sign on behalf of the manufacturer:

A handwritten signature in black ink that reads "Patrick Finch". The signature is written in a cursive style and is positioned above a horizontal line.

Quality Assurance Representative

