
OPERATION & SERVICE MANUAL

MODEL: 03-5813-0000

PIAGGIO P180 TAILSTAND





1.0 DESCRIPTION

This Tronair Tailstand incorporates the following quality features:

- o Steel construction
- o Easily maneuverable
- o Vertically adjustable to within plus or minus 1/4"
- o May be disassembled for easy replacement of parts or shipment

2.0 USAGE

The purpose of this Tailstand is to support aircraft fuselage during maintenance.

3.0 ASSEMBLY INSTRUCTIONS

3.1 GENERAL INFORMATION

This product should be assembled and/or repaired using good workmanship practices and proper tools. Bolts and elastic stopnuts should be tightened to a torque not to exceed industry standards for grade '5' bolts. 3/8-24 bolts should be tightened to 35 ft. lbs. and 1/2-20 bolts tightened to 85 ft. lbs.

All replacement parts must be the same as or equal to the original parts supplied.

3.2 PRE-USE CHECKS

Refer to the Tailstand illustrated parts breakdown to identify and assure all parts are present.

o Generally check over the unit to assure the tightness of all nuts, bolts and screws with extension collapsed.

3.3 ASSEMBLY STEPS

o Slide cradle assembly inside base assembly. Adjust to desired height and insert lock pin.


11/91

PARTS LIST

PRODUCT:

MODEL: 03-5813-0000 PIAGGIO P180 TAILSTAND

DATE: 11/21/91



ITEM	PART NUMBER	DESCRIPTION	QTY.
1	Z-2528-00	ASSEMBLY, CRADLE	1
2	G-1100-107534	BOLT, HEX HD 3/8-24 X 3 1/2	2
3	G-1250-1070N	FLATWASHER, 3/8	4
4	G-1202-1075	STOPNUT, 3/8-24 ELASTIC	2
5	Z-2436-00	WELDMENT, CRADLE	1
6	G-1311-01	PIN, LOCK	1
7	Z-2508-00	WELDMENT, TRIPOD	1



AIRCRAFT GROUND SUPPORT EQUIPMENT

South 1740 Eber Road • Holland, Ohio 43528 (419) 866-6301 • TWX: 810-440-2839