

# 25 Ton Fixed Height Tripod Jack

## Model 7225A

The Model 7225A Fixed Height Tripod Jack is a 25 ton capacity, single stage hydraulic jack designed primarily for use in aircraft maintenance. It consists of a tripod structure, hydraulic cylinder/reservoir assembly, adjustable hand pump and swivel casters.

The jack leg pads are raised off the ground by spring loaded casters. The casters will retract and the pads rest on the ground when a load is applied to the jack.

Model 7225A is built to withstand harsh environmental conditions and rugged use, and to provide many years of continuous service. Our customers are guaranteed a quality product with each purchase and are assured of our continued product support whenever and wherever the need arises.

### Standard Features:



- Manual hand pump with high, medium and low pressure operating positions
- Heavy duty swivel casters
- Rain hat (covers jack upper head)
- Hard chrome plated cylinder bore
- All unpainted parts are plated to resist corrosion
- Skydrol resistant paint (safety yellow)
- Factory proof load @ 150% of rated capacity
- Shipping skid
- 3 year standard warranty
- Shipment on domestic skid

### Optional Features:

- Air operated hydraulic pump
- Load gauge for load indication (reads tons/psig)
- Tow handle for ease of towing
- Export crating
- Customer specified paint color

# 25 Ton Fixed Height Tripod Jack

## Model 7225A



For more information contact: [sales@malabar.com](mailto:sales@malabar.com)

# 25 Ton Fixed Height Tripod Jack

## Model 7225A

### Specifications:

Rated Capacity.....	25 tons (22.7 m. tons)
Side Load .....	15% of vertical load
Roll Under Height.....	43 inches (1092 mm)
Low Height .....	42 inches (1067 mm)
Hydraulic Lift .....	32 inches (813 mm)
Extension Screw .....	10 inches (254 mm)
Total Extended Height .....	84 inches (2134 mm)
Oil Pressure at Rated Capacity .....	3500 psig (246 kg/sq cm)
Safety Pop-off Valve set at .....	27.5 tons (24.9 m. tons)
Proof Load.....	37.5 tons (34.0 m. tons)
Reservoir Capacity.....	2.2 gallons (8.3 liters)
Hydraulic Fluid .....	MIL-PRF-5606 or equivalent
Maximum Towing Speed .....	5 mph (8 km/h)
Approximate Jack Net Weight .....	575 lbs (261 kg)

### Model 7225A Typical Aircraft Applications:

Forward Fuselage	Wing	Mid Wing
BAC1-11	BAC1-11, GI, GII, GIII, GIV, GV, GVI, GVII, SF340	BAC1-11

### Optional Equipment Codes:

*(Specify with order)*

- AP: Air Operated Hydraulic Pump
- GA: Load Gauge
- TH: Tow Handle
- SPC: Special Paint Color (yellow is standard)
- 7225APK: Repair Kit

### Packaging Codes & Options:

*(Specify with order)*

- : Domestic Skid – Jack Set-up
- KD: Domestic Skid – Jack Knocked Down (Additional Cost)
- EC: Export Crate – Jack Set-up (Additional Cost)
- ECKD: Export Crate – Jack Knocked Down (Additional Cost)

# 25 Ton Fixed Height Tripod Jack

## Model 7225A

### Shipping Data:

NOTE: Unless otherwise specified, Model 7225A jack is shipped on a wood skid in the set-up condition.  
Refer to Malabar Tripod Jack Shipping Supplement for additional packaging information.

Packaging Code	Length inches (mm)	Width inches (mm)	Height inches (mm)	Weight lbs (kg)
-	63 (1600)	54 (1372)	50 (1270)	675 (306)
KD	68 (1727)	40 (1016)	28 (711)	675 (306)
EC	65 (1651)	59 (1499)	53 (1346)	925 (420)
ECKD	70 (1778)	45 (1143)	31 (787)	825 (374)